



# SMART TRANSFORMATIONS

## Commercial Tile

TEST METHOD	PROPERTY	SPECIFICATION
	<b>CONSTRUCTION</b>	100% ecofi <sup>®</sup> Dura-Lock <sup>®</sup> Technonogy Foss Solution Dyed POLYESTER with Peel-and-Stick Backing (Made from 100% post-consumer plastic bottles) Contains NATURION <sup>®</sup> Antimicrobial Technology
FTM NW508 (ASTM D3776)	<b>TOTAL WEIGHT</b>	32.0 oz/yd <sup>2</sup> +/-3.0 oz/yd <sup>2</sup>
	<b>TILE SIZE</b>	Length 24 in Width 24 in
PILE (FTM NW523)	<b>PILE HEIGHT</b>	3.0 mm +/-0.5 mm
CAL 1350 (ASTM D5166)	<b>VOC EMISSIONS</b>	Meets All Requirements
PILL TEST DOC (FF 1-70)	<b>FLAMMABILITY</b>	PASS
RADIANT PANEL (ASTM E648-14a)	<b>CRITICAL RADIANT FLUX</b>	NFPA 101 Classification: Class 1
SMOKE DENSITY (ASTM E662-13d)	<b>OPTICAL SMOKE DENSITY</b>	PASS
VISUAL	<b>COLOR</b>	Variety of Colors Available
VISUAL	<b>APPEARANCE</b>	Choice of Structured Surface Patterns

CWF Flooring, Inc. 38325 6th Street East Palmdale, CA 93550 Tel. 1-661-273-8700  
[www.PeelandStickCarpetTiles.com](http://www.PeelandStickCarpetTiles.com) [Sales@PeelandStickCarpetTiles.com](mailto:Sales@PeelandStickCarpetTiles.com)